

# SIEVERT PRO 88 TORCH HEATING KIT ASSEMBLY INSTRUCTIONS

This document is the instruction to ensure that the orange hose assembly, Part Number 1811346, has a gas tight connection when connected to the Bromic LPG regulator and Sievert Pro 88 handle.



## CONNECTION OF HOSE ASSEMBLY

Connect by hand the M14 nut on the hose assembly to the Sievert Pro 88 handle outlet. Then **spanner** tighten by turning in clockwise direction.

Connect by hand the 5/8 - 18 UNF nut (left hand thread) to the regulator outlet. Then **spanner** tighten by turning in ant-clockwise direction.

## CONNECTION TO LPG CYLINDER

Connect by hand the POL nut (left hand thread) regulator inlet to an LPG cylinder with a POL outlet, then **spanner** tighten by turning in ant-clockwise direction.

## WARNING --- LEAK TEST BEFORE USE

Use soapy water or LA-CO Visu-Glow Leak Detector to verify connections are gas tight.

	<p>Safety hazards may exist when using this product.                      Only to be used by trained and skilled personnel.                      Use only in ventilated areas                      Do not use if any component of the kit is damaged                      Always disconnect the hose from the cylinder when kit is not in use.                      Protective personal gear must be used when operating this unit                      Protect the kit from damage when in storage or during transportation.</p>		